



**Notes:**

Honeywell FC100A1029\* Residential Air Cleaner replacement filters are 5" deep pleated pleats that are specifically designed to replace other 16" x 25" ducted air products. Honeywell FC100A1029\* is available in 3 efficiencies including: MERV 8, MERV 11, and Carbon medias.

**Performance Data**

Product Code	ASHRAE 52.2 - 1999			Initial Resistance "w.g." @ 836 cfm	Final Resistance "w.g." @ 836 cfm
	MERV Value	E1 %	E2 %		
0215HW2940	8	n/a	n/a	0.08	.50
0215HW29MQP	11	n/a	n/a	0.1	.50
0215HW29OB	n/a	n/a	n/a	0.07	.50

**Part Number Guide**

Product Code	Description	Nominal Dimensions	Actual Frame Dimensions
0215-HW2940	Type 40 - MERV 8	16" x 25" x 5"	15.875" x 24.75" x 4.25"
0215-HW29MQP	MQP - MERV 11	16" x 25" x 5"	15.875" x 24.75" x 4.25"
0215-HW29OB	Odor Ban	16" x 25" x 5"	15.875" x 24.75" x 4.25"

\*Trade names and company names are used for identification purposes only.

Characteristics	Honeywell FC100A1029*				
Filter Media - Particulate	100% synthetic gradient media, electrostatically charged	Filtration Manufacturing, Inc. 47 J Faris Drive Andalusia, AL 36421			
**Filter Media - Odor Ban	Fine carbon powder bonded to lofted polyester media				
Filter Support Grid	30 gauge galvanized expanded metal grid	Phone: (800) 239-8413 Order Fax: (800) 239-9798 Sales Fax: (800) 239-9798			
Frame	Moisture resistant 28 point beverage board				
Assembly Technique	Media pack totally bonded to frame	<b>FMI OEM</b> <b>Honeywell FC100A1029* - 16" x 25" x 5"</b>			
Max. Temperature	180°F (82°C) continuous service, Peaks 225°F (107°C)				
Max. Humidity	Resistant to 100% R.H.	DR JJS	Date 15 Jun 04	Dwg No. <b>Q-110016</b>	Revision
		CK RBB	Date 15 Jun 04		